



STP® DEX ANTIFREEZE/COOLANT

TECHNICAL DATA

Since 1954, STP® has been the premier American brand name for automotive additives, lubricants and performance products in the USA. STP® DEX Antifreeze/Coolant is an ethylene glycol automotive engine coolant based on a patented extended life carboxylate inhibitor system. This superior quality engine coolant is free of borates, nitrites, silicates, and amines. It protects all cooling system metals including aluminum, as well as rubber hoses, gaskets and plastics. Recommended for initial fill or top-off in all gasoline and diesel engines where a DEX-COOL®* type products are in use or are required.



Performance, Features & Benefits:	<ul style="list-style-type: none"> • Premium extended life antifreeze/coolant • Free of borates, nitrites, silicates, and amines • Protects against corrosion of all cooling system metals • Compatible with most major brands of extended life Organic Acid Technology (OAT) type antifreeze/coolant formulated to meet the DEX-COOL®* requirement (GM 6277M) • Protects against corrosion of all cooling system metals • Protects against winter freeze up and summer boil over 																				
Package Size Offerings	<table border="1"> <tr> <td>Concentrate 3x1 Case</td> <td>Part #11087</td> <td>UPC - 652138110870</td> </tr> <tr> <td>Concentrate Drum</td> <td>Part #10269</td> <td>UPC - 652138100253</td> </tr> <tr> <td>Concentrate Tote</td> <td>Part #10267</td> <td>UPC - 652138100260</td> </tr> <tr> <td>Ready-To-Use 3x1 Case</td> <td>Part #11088</td> <td>UPC - 652138110887</td> </tr> <tr> <td>Ready-To-Use Drum</td> <td>Part #10274</td> <td>UPC - 652138100277</td> </tr> <tr> <td>Ready-To-Use Tote</td> <td>Part #11214</td> <td>UPC - 652138100284</td> </tr> </table>	Concentrate 3x1 Case	Part #11087	UPC - 652138110870	Concentrate Drum	Part #10269	UPC - 652138100253	Concentrate Tote	Part #10267	UPC - 652138100260	Ready-To-Use 3x1 Case	Part #11088	UPC - 652138110887	Ready-To-Use Drum	Part #10274	UPC - 652138100277	Ready-To-Use Tote	Part #11214	UPC - 652138100284		
Concentrate 3x1 Case	Part #11087	UPC - 652138110870																			
Concentrate Drum	Part #10269	UPC - 652138100253																			
Concentrate Tote	Part #10267	UPC - 652138100260																			
Ready-To-Use 3x1 Case	Part #11088	UPC - 652138110887																			
Ready-To-Use Drum	Part #10274	UPC - 652138100277																			
Ready-To-Use Tote	Part #11214	UPC - 652138100284																			
Aluminum Compatibility	Yes																				
Contains Bitterant	Yes																				
Base Fluid	100% Virgin Ethylene Glycol																				
pH, 50% Volume Solution	8.0-9.0																				
Product Color	Orange																				
Specifications, Approvals & Recommendations*†	ASTM D3306	ASTM D4985	GM 6277M* (DEX-COOL®*)																		
<small>*For a full list of performance specifications, visit www.stpcoolant.com.</small>																					
Recommended Change Interval	Up to 5 Years/150,000 Miles																				

Shipping Information	Cases	Steel Drums	Totes
Package Quantity	3x1 Gallons	55 Gallons	275 Gallons
Package Dimensions	12.5"x7.8"x12"	23.5"Dx34.5"H	45.3"x40"x48"
Gross Container Weight - Concentrate	≈31 Pounds	≈553 Pounds	≈2711 Pounds
Gross Container Weight - 50/50	≈29 Pounds	≈530 Pounds	≈2595 Pounds
Gross Weight on Pallet - Concentrate	≈2247 Pounds	≈2262 Pounds	≈2711 Pounds
Gross Weight on Pallet - 50/50	≈2139 Pounds	≈2170 Pounds	≈2595 Pounds
Quantity Per Pallet	72	4	1
Pallet Dimensions	40"x48"x52.3"	45"x45"x39.4"	40"x48"x45.3"
Weight Per Gallon - Concentrate	≈9 Pounds	≈9 Pounds	≈9 Pounds
Weight Per Gallon - 50/50	≈9 Pounds	≈9 Pounds	≈9 Pounds

All reasonable care has been taken to ensure that the information herein is accurate as of the date of printing. The test results listed are typical properties only. Formula and blending changes may result in slight color and appearance changes. *DEX-COOL® is a registered trademark of General Motors Corporation. This product is not manufactured for or licensed by General Motors Corporation.

STPPD5052218



KOST® USA, Inc. recommends to always properly dispose of spent coolant. Contact your state or local municipality for instructions on proper disposal to protect our environment. If a coolant spill occurs, call local authorities and ask for proper instruction on how to clean up the spill.

