

## STP® XTEND HIGH MILEAGE EXTENDED LIFE ANTIFREEZE







KOST® USA, Inc. recommends to always properly dispose of spent coolant. Contact your state or local municipality for instructions on proper disposal to protect our environment. If a coolant spill occurs, call local authorities and ask for proper instruction on how to clean up the spill.

## TECHNICAL DATA

Since 1954, STP® has been the premier American Brand Name for automotive additives, lubricants and performance products in the USA. STP® XTEND HIGH MILEAGE Antifreeze/Coolant Ready-To-Use is an advanced formulation that meets or exceeds ASTM requirements. This premium ethylene glycol-based engine coolant is free of phosphates, borates, nitrites, silicates, and amines. It protects all cooling system metals including aluminum, as well as rubber hoses, gaskets and plastics and contains 65% more corrosion inhibitors\* than other extended life antifreeze/coolants on the market. Recommended for initial fill or top-off in all makes and models of foreign and domestic cars and light duty trucks over 75,000 miles, providing for maximum protection in vehicles that need it most.

Performance, Features & Benefits:	65% more inhibitors* to protect your older vehicle's engine     For cars and light duty trucks with over 75,000 odometer miles     Protects against winter freezing and summer boil over     Free of phosphate, borates, nitrites, silicates, and amines     Compatible with any antifreeze/coolant, regardless of color     Protects against corrosion of all cooling system metals			
Package Size Offerings	Concentrate 3x1 Case Concentrate Drum Concentrate Tote Ready-To-Use 3x1 Case Ready-To-Use Drum Ready-To-Use Tote	Part #11515 Part # Call Part # Call Part #11514 Part # Call Part # Call	UPC - 652138103216 UPC - 652138 UPC - 652138 UPC - 652138103223 UPC - 652138 UPC - 652138	
Aluminum Compatibility	Yes			
Contains Bitterant	Yes			
Base Fluid	100% Virgin Ethylene Glycol			
pH, 50% Volume Solution	8.0-9.0			
Product Color	Yellow			
Specifications, Approvals & Recommendations*†	ASTM D3306  *For a full list of performance specifications, visit www.stpcoolant.com.*Increase in number of conventioanl inhibitors versus STF® ALL Global Extended Life Antifreeze/Coolant			
Recommended Change Interval	Up to 5 Years/150,000 Miles			

<b>Shipping Information</b>	Cases	Steel Drums	Totes
Package Quantity	3x1 Gallons	55 Gallons	275 Gallons
Package Dimensions	12.5"x7.8"x12"	23.5"Dx34.5"H	45.3"x40"x48"
Gross Container Weight - Concentrate Gross Container Weight - 50/50	≈31 Pounds ≈29 Pounds	≈553 Pounds ≈530 Pounds	≈2711 Pounds ≈2595 Pounds
Gross Weight on Pallet - Concentrate Gross Weight on Pallet - 50/50	≈2247 Pounds ≈2139 Pounds	≈2262 Pounds ≈2170 Pounds	≈2711 Pounds ≈2595 Pounds
Quantity Per Pallet	72	4	1
Pallet Dimensions	40"x48"x52.3"	45"x45"x39.4"	40"x48"x45.3"
Weight Per Gallon - Concentrate Weight Per Gallon - 50/50	≈9 Pounds ≈9 Pounds	≈9 Pounds ≈9 Pounds	≈9 Pounds ≈9 Pounds

All reasonable care has been taken to ensure that the information nerein is accurate as of the date of printing. The test results listed are typical properties only, Formula and blending changes may result in slight color and appearance changes.

STPPDS052218

